


A004-19 Antique Ash Oak



Installation Methods



Ashlar



Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see

www.interface.com.cn/page/disclaimer

Product Textured Woodgrains **Colour** Antique Ash Oak **Collection** Level Set

Product Number A004

Product Specifications

Product Construction High Performance Luxury Vinyl Tile

Wear Layer Thickness 0.55 mm

Total Thickness (Metric) 4.5 mm

Classification EN 651 Class 33(heavy contract)
EN 651 Class 42(light industrial general)

Finish CERAMOR™ UV Stabilized Ceramic Bead Coating

Nominal Dimensions 25cm x 1m

Performance Specifications

Critical Heat Flux AS ISO 9239-1 >7kW/m²

Smoke Rate AS ISO 9239-1 <750%.min

Size, Tolerance ISO 24342 <400 mm <0.25 mm
ISO 24342 >400 mm < 0.35 mm

Dimensional Stability ISO 23999 <0.25%

Thickness ISO 24346 Average value + 0.20mm

Resistance to Light ISO 105-B02 ≥6

Resistance to Heat ASTM F1514 ΔE< 8 avg Max

Resistance to Chemicals EN-ISO 26987 Pass

Reaction to Fire EN ISO 13501-1 Class BFI-S1

VOC Test ISO 10580 Pass

Flexibility ISO 24344 Method A Pass

Static Load ASTM F970 ≤0.005' with 1500 psi

Castor chair ISO 4918 Pass

Thermal Conductivity EN 12667 0.16 W/mK

Static Electrical EN 1815 <2kV

Slip Resistance AS 4586:2013 R10

Environmental Specifications

Ingredients and Life Cycle Impacts [EPD for 4.5mm LVT](#)

NSF Sustainable Carpet NSF/ANSI 332, Meets Certification Guidelines

LEED V4 Contributes to IEQ: Low Emitting Materials
M&R: EPD and EPR

Recycled Content % 39 %

Embodied Carbon (Cradle to Gate)	9.2 kg CO ₂ eq./m ²
----------------------------------	---

Technical Information

Installation	See Interface LVT Installation Guidelines online
Maintenance	See Interface LVT Maintenance Guidelines online
Warranty	15 Year Standard LVT Product Warranty
