


B001-06 Blonde



Installation Methods



Ashlar



Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com.cn/page/disclaimer

Product Steady Stride Woodgrains Colour Blonde Collection

Product Number B001

Product Specifications

Product Construction	Luxury Vinyl Plank
Wear Layer Thickness	0.5 mm
Total Thickness (Metric)	3.0 mm
Classification	ASTM F1700 / Class III Printed Vinyl Tile
Finish	Ceramic Coating
Nominal Dimensions	12.5cm x 100cm

Performance Specifications

Critical Heat Flux	ASTM E648 Class I
Size, Tolerance	ISO 24342 <400 mm <0.25 mm ISO 24342 >400 mm < 0.35 mm
Dimensional Stability	ASTM F2199 Passes
Thickness	ASTM F386 Passes
Resistance to Light	ASTM F1515 Passes
Resistance to Heat	ASTM F1514 $\Delta E < 8$ avg Max
Resistance to Chemicals	ASTM F925 Passes
Flexibility	ASTM F137 Passes
Static Load	ASTM F970 > 250 psi
Static Electrical	EN 1815 <2kV

Environmental Specifications

Ingredients and Life Cycle Impacts	EPD for 3.0mm LVT
NSF Sustainable Carpet	NSF/ANSI 332, Meets Certification Guidelines
LEED V4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR
Recycled Content %	39 %
Embodied Carbon (Cradle to Gate)	7.27 kg CO ₂ eq./m ²

Technical Information

Installation	See Interface LVT Installation Guidelines online
Maintenance	View recommended Interface Maintenance Guidelines online
Warranty	10 Year Standard LVT Product Warranty