


7414-008-000 Driftwood



Installation Methods



Non Directional

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com.cn/page/disclaimer](http://www.interface.com.cn/page/disclaimer)

**Product** B601 **Colour** Driftwood **Collection** Net Effect

|                |      |
|----------------|------|
| Product Number | 7414 |
|----------------|------|

**Product Specifications**

|                         |                                   |
|-------------------------|-----------------------------------|
| Product Construction    | Tufted Textured Loop              |
| Yarn System             | 100% Recycled Solution Dyed Nylon |
| Dye Method              | 100% Solution Dyed                |
| Soil/Stain Protection   | <a href="#">Protekt2®</a>         |
| Preservative Protection | Intersept®                        |

**More Product Specifications**

|                   |                   |
|-------------------|-------------------|
| Machine Gauge     | Tapestry          |
| Stitches          | 28.5/10cm 7.2 /in |
| Pile Thickness    | 5.0mm ±0.5mm      |
| Total Thickness   | 8.5mm ±0.5mm      |
| Backing Structure | GlasBac® RE       |

**Performance Specifications**

|                                         |                                                                                    |
|-----------------------------------------|------------------------------------------------------------------------------------|
| Area of Use                             | Commercial General Use                                                             |
| Stability - Delaminating                | ASTM D3936 ≥ 3.0 lbs/in<br>GB/T 26843 ≥ 26 N                                       |
| Stability - Dimensional Stability       | ISO 2551 ≤ ± 0.1%<br>QB/T 2755 ≤ 0.1%                                              |
| Stability - Tuft Bind                   | QB/T 1090 ≥ 24 N (QB/T 2755)<br>ISO 4919 > 30 N                                    |
| Wear - Castor Chair                     | QB/T 2755 ≤ 0.15%<br>EN 985 > 2.4 Rating @25,000 cycles                            |
| Wear - Vetterman Drum                   | GB/T 26844 ≥ 3.0 at 22000 cycles<br>TWC-TM247/251/284 Colour: ≥3 & Structure: ≥3   |
| Colour Fastness to Light                | GB/T 8427 ≥ 4-5<br>AATCC 16 Part 3 ≥ 4 @ 60 Hours                                  |
| Colour Fastness to Rubbing and Crocking | GB/T 3920 ≥ 4-5<br>AATCC 165 ≥ 4 (Wet & Dry)                                       |
| Colour Fastness to Water                | AATCC 107 ≥ 4<br>GB/T 5713 ≥ 4-5                                                   |
| Flammability - Methanamide Pill         | GB/T 11049 ≤ 25.4 mm<br>ASTM 2859 - 7 of 8 passing                                 |
| Flammability - Radiant Panel            | GB/T 11785 B1 CHF≥ 4.5 kW/m <sup>2</sup> (GB 8624)<br>ASTM E648 > .45 watts/sq. cm |
| Flammability - Smoke Density            | ASTM E662 < 450<br>GB/T 11785 s1 ≤ 750 %.min (GB 8624)                             |
| Antistatic                              | AATCC 134 < 3.0 kV<br>GB/T 18044 ≤ 2.0 kV                                          |

|                        |                                                                                         |
|------------------------|-----------------------------------------------------------------------------------------|
| Lifetime Antimicrobial | AATCC 174 Parts II & III 99% reduction/No mold 7 Days<br>ASTM E2471 Complete Inhibition |
|------------------------|-----------------------------------------------------------------------------------------|

## Generic Tests

|                    |                                                                 |
|--------------------|-----------------------------------------------------------------|
| Acoustic – Nylon   | Absorption Coefficient - NRC 0.0 - 0.2                          |
| Dynamic Loading    | ISO 2094 < 15% Thickness loss<br>QB/T 1091 < 15% Thickness loss |
| Static Loading     | ISO 3415 < 15% Thickness loss<br>QB/T 1092 < 15% Thickness loss |
| Green Carpet (VOC) | ASTM D5116 Accredited<br>ISO 10580 Accredited                   |
| Thermal Resistance | ASTM C518 R Value 0.5                                           |

## Environmental Specifications

|                                    |                                                                 |
|------------------------------------|-----------------------------------------------------------------|
| Recycled Content %                 | 75%                                                             |
| Pre-Consumer (Total)               | 52%                                                             |
| Post-Consumer (Total)              | 23%                                                             |
| Other Environmental Claims         | <a href="#">View Environmental Accreditations</a>               |
| Ingredients and Life Cycle Impacts | <a href="#">Environmental Product Declaration - GlasBac® RE</a> |
| End of Life                        | Carpet to Carpet Recycling                                      |
| Embodied Carbon (Cradle to Gate)   | 7.01 kg CO <sub>2</sub> eq./m <sup>2</sup>                      |

## Technical Information

|                        |                                                                               |
|------------------------|-------------------------------------------------------------------------------|
| Installation           | <a href="#">View recommended Interface Installation Guidelines online</a>     |
| Maintenance            | <a href="#">View recommended Interface Maintenance Guidelines online</a>      |
| Reclamation            | <a href="#">View details on our ReEntry™ Program</a>                          |
| Warranty               | <a href="#">15 Year Standard Warranty</a>                                     |
| Manufacturing Location | <a href="#">ISO9001&amp;14001&amp;45001 Certified Plant in Taicang, China</a> |